KÖNIG ELECTRONIC

Your World, Our Technology

LNB Monoblock Twin

Voor Astra 19.2° en Hotbird 13°

USP's:

- Voor Astra 19.2°
- Voor Hotbird 13°
- Realistisch ruisgetal van 0.6 dB
- DiSEqC V 2.0

Algemene informatie:

Universeel 40 mm monoblock LNB met een realistisch ruisgetal van 0.6 dB en DiSEqC versie V 2.0. Deze unieke single uitvoering ontvangt de Hotbird 13° en Astra 19,2° op 2 ontvangers. Het Astrablock werkt optimaal met een 80 cm schotel, maar kan ook uit de voeten met een 60 cm schotel. Geschikt voor High Definition ontvangst.

Specificaties:

• Feed diameter:	40mm
• Uitgangen:	2
• Satelliet A:	Hotbird 13°E
• Satelliet B:	Astra 19.2°E
• RF input:	Low band: 10.7~11.70 GHz High band: 11.7~12.75 GHz
• IF output:	Low band: 950~1950 MHz High band: 1100~2150 MHz
• Local oscillator:	Low band: 9.75 GHz High band: 10.6 GHz
• Stabiliteit:	± 1 MHz (Max.) @ kamertemperatuur/± 3 MHz (Max.) @ -40°C ~ +60°C
• Ruisgetal (typ.):	Low band 0.6 dB High band 0.6 dB
• Kruispolarisatie (typ.):	20 dB
• Max. DC verbruik:	120 mA
• Werkvoltage:	Verticaal 11.5~14 V DC Horizontaal 16~19 V DC
• Bandschakelaar:	Low band: 0 Hz High band: 22 KHz ± 4 KHz
• Temperatuurbereik:	-55°C~ +80°C

Verkoopinformatie:

Ordercode:	**LNB1-MONOTKN**
Omschrijving:	LNB Monoblock twin
Verpakking:	Blister
TARIC code:	8543709099

CE

5 412810 146093

	Verpakt per	LxBxH (mm)	Gewicht
Single	1 stuk	215x185x100	592 gr
Master	20 stuks	690x310x410	13.5 kg

©2011 König®. All rights reserved. König® is a registered trademark.
Specifications are subject to modification without prior notice. Contents may differ slightly from what is shown.
König can not be held responsible, nor liable for the information contained in this document.