KÖNIG ELECTRONIC

Your World,
Our Technology

Quattro LNB

For multiswitch

USPs:

- Very low noise figure

General information:

Superior König quattro LNB with a noise figure of only 0.6 dB! Especially suitable for use in installations that need the highest signal strength and quality possible.

Specifications:

• Feed diameter:	40 mm
• Outlet:	4 (HH/HV/LH/LV)
• RF input:	Low: 10.7 ~ 11.70 GHz High: 11.7 ~ 12.75 GHz
• IF output:	Low: 950 ~ 1950 MHz High: 1100 ~ 2150 MHz
• Local oscillator:	Low: 9.75 GHz High: 10.6 GHz
• Stability:	± 3 MHz (max.) @ -40°C ~ +60°C
• Noise figure (typ.):	Low: 0.6 dB High: 0.6 dB
• Cross polarization (typ.):	20 dB
• DC current cons. max:	250 mA
• Operating voltage:	11.5 ~ 21 V DC
• Band switching:	Low: 0 Hz High: 22 KHz ± 4 KHz
• Temperature range:	-55°C~ +80°C

Sales information:

Order code:	**LNB1-QUATTROKN**
Description:	Universal quattro LNB
Packaging:	Blister
TARIC code:	8543709099

CE

5 412810 146123

	Quantity	LxWxH (mm)	Weight
Single	1 pc	190x170x080	297 g
Master	20 pcs	395x380x380	7.1 kg

©2011 König®. All rights reserved. König® is a registered trademark.
Specifications are subject to modification without prior notice. Contents may differ slightly from what is shown.
König can not be held responsible, nor liable for the information contained in this document.